SHIELD Scientific
compliance comfort protection

SHIELDskin™ Bright Latex 300

Powder Free Extra Length Ambidextrous Non-Sterile 30 cm Textured Latex Gloves

PPE Category III (Complex Design) according to Council Directive 89/686/EEC

Fully compliant to the latest PPE norms – EN 374:2003 "Protective gloves against chemicals and micro-organisms"

PRODUCT INFORMATION

Size	Catalogue Numbers	Applicable Norms with Pictograms			
Extra Small (XS/6)	67 4251	EN 374:2003	EN 374:2003 Level 3	LATEX	CE 0120*
Small (S/7)	67 4252				
Medium (M/8)	67 4253				
Large (L/9)	67 4254	EN 420:2003 + A1:2009			
Extra Large (XL/10)	67 4255	Also meets or exceeds EN 455-1:2000, EN 455-2: 2015, EN 455-3:2015 & EN 455-4:2009 relating to Council Directive 93/42/EEC for Medical Devices			

* SGS UK Ltd (Notified Body No: 0120), Unit 202B Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

Material: Natural Rubber Latex. Contains 50 micrograms or less of total water extractable protein per gram, using the EN 455-3:2015 / ASTM D5712-15 Modified Lowry Method. Typical measurements for latex protein are ≤30µg/g as per Modified Lowry Method.

Design: Natural colour, ambidextrous, beaded cuff and fully textured.

Packaging: Fifty (50) gloves per dispenser. Dispenser is varnished for enhanced compatibility with laboratory environments. Gloves are flat-packed. Ten (10) dispensers per case. Packed in a double-walled shipping case.

PHYSICAL PROPERTIES

Characteristics	Value	Test Method
Freedom from holes	<0.65 AQL[1]	EN 374:2003

[1] AQL as defined per ISO 2859 for sampling by attributes

Tensile Properties	Tensile Strength (min)	Typical	Ultimate Elongation	
- Before Aging	>9.0N, min.	>9.0N	700%, min.	EN 455-2: 2015, ASTM D573-04(2015) and ASTM D 412-15a
- After Accelerated Aging	>6.0N, min.	>9.0N	500%, min.	

Dimensional	Measured Point	mm	mil	
- Nominal Thickness	Middle Finger	0.16	6.2	ASTM D3767-03(2014)
	Palm	0.14	5.3	
	Cuff	0.10	3.9	
- Length	300mm, min.		305mm, typical	EN 420:2003 + A1:2009

Palm Widths

- Nominal Width (mm) (+/- 5 mm)	XS/6	S/7	M/8	L/9	XL/10	EN 455-2:2015
	75	85	95	106	116	

Hand Circumference

- Nominal circumference (mm)	XS/6	S/7	M/8	L/9	XL/10	EN 420:2003 + A1:2009
	152	178	203	229	254	

ADDITIONAL DATA

- **Non-detectable levels of chemical allergens** using aqueous solution extraction (Phosphate buffered solution) and High Performance Liquid Chromatography (HPLC) assay method for quantitative analysis.
- **Biocompatibility** demonstrated by the Primary Skin Irritation Test CPSC 16-II-1500 and dermal sensitization test ASTM F720-13.
- **Free of Thiazoles and Thiurams** – these chemical accelerators are excluded from the manufacturing process.
- **Powder free** to minimize the potential consequences of powder-borne dermatitis. Residual powder content is 1.0 mg/glove (typical) with a limit of 2.0 mg/glove (ISO 21171:2006 "Medical gloves – Determination of removable surface powder").
- **Micro - organism and virus resistant** – passes highest level of micro - organism resistance per EN 374-2:2014 (Performance level 3, AQL <0.65 and inspection level G1 according to 1000ml water test) and passes viral penetration test using Phi-X 174 bacteriophage (ISO 16604:2004 Procedure B & ASTM F1671-97b).
- **Extensively tested for chemical permeation** according to EN 16523-1:2015 (please refer to chemical resistance guide on website - www.shieldscientific.com/public/chemical-resistance-guide).

QUALITY SYSTEMS

- Manufactured in accordance with ISO 9001:2015 and ISO 13485:2016.

"SHIELDskin™, A revolution in Glove Technology"

SHIELD Scientific
compliance comfort protection

www.shieldscientific.com

SHIELDskin™ is a trademark of SHIELD Scientific © 2007 Copyright SHIELD Scientific B.V. – All Rights reserved
Dr. Willem Dreeslaan 1 ◦ 6721 ND Bennekom ◦ The Netherlands - Phone +31 (0)317 700 202 ◦ Fax +31 (0)318 503 742 ◦ E-mail: Info@shieldscientific.com